

Kilews 5200 ESD Electric Screwdriver

SKU: 290-5200L



Features & Benefits

- ◆ **Low voltage, automatic clutch system** for stable, high-efficiency performance.
- ◆ **Stepless torque adjustment (1-12 Kgf.cm)**, with a rotation speed of 700 to 1000 RPM for precise control.
- ◆ **High-tech DC motor with Japanese parts** ensures durability and smooth operation.
- ◆ **Ergonomic, slip-resistant housing** for fatigue-free use, even over long periods.
- ◆ **ESD-safe design** to prevent electrostatic discharge damage to sensitive components.
- ◆ **Lightweight:** Weighs only 480g with a length of 230mm for ease of use and control.
- ◆ **Torque fixing ring (KC-6C)** for precise torque control.
- ◆ Featuring a low-voltage, automatic clutch system, this screwdriver is ideal for long hours of use with high stability, ensuring consistent performance even with fluctuating voltage

About the Kilews 5200 ESD Electric Screwdriver

The Kilews 5200 ESD Electric Screwdriver is an advanced tool designed for high-precision work in electronics and assembly. Featuring a low-voltage, automatic clutch system, this screwdriver is ideal for long hours of use with high stability, ensuring consistent performance even with fluctuating voltage.

With an ergonomic, two-tone housing that is temperature, vibration, and slip-resistant, the screwdriver offers comfortable handling and reduces fatigue during prolonged use.

It's perfect for tasks involving high-tech devices like PCs, laptops, and gaming consoles.

- **High tech DC motor with Japanese parts. Fast start with low power. Stable torque within accuracy of $\pm 3\%$.**
- **0-8 stepless torque adjustment, rotation speed selected by switches Hi & Lo or VR (freely adjust).**
- **Suitable for high-tech PC, laptop, Game Cube, etc. Torque fixing ring (KC-6C) can be set to fix torque.**
- **Bit type: "B" in SS 6.35mm/1/4" Hexagon Type**
- **Bits Included(2): S1/4*50*4.5 Pozi 1#(9.5mm) and S1/4*50*4.5*Pozi 2#(9.5mm)**
- **Trigger series meets UL, CE approval, screwdriver is ESD safe.**

Specifications

Property	Detail
Torque	1-12 (Kgf.cm) 0.89~10.44 (Lbf.in) - 0.1~1.18 (N.m)
Bit Type	1/4 HEX, suitable for various screws, including machine and tapping screws.
Versatile torque range	0.1-1.18 N.m (0.89-10.44 Lbf.in).
Application	ESD-protected areas, electronics mfg, cleanrooms