

# Qualitek PF608 No Clean Paste Flux - Lead Free

SKU: 390-83 | Sizes: 13g/10cc Syringe, 40g/30cc Syringe



## Features & Benefits

- ◆ **Lead-Free Formula:** Ideal for both high-temperature lead-free and conventional Sn/Pb alloys.
- ◆ **Fast Wetting Action:** Provides excellent fluxing activity for rapid and thorough solder joint formation.
- ◆ **Clear, Non-Conductive Residue:** Leaves a clean, non-tacky residue that requires no post-soldering cleaning.
- ◆ **High Tack:** Minimises component skewing during assembly for precise soldering.
- ◆ **Reflowable:** Can be reflowed with peak temperatures up to 270°C in air, with no nitrogen required.
- ◆ **Available Sizes:** Syringe options of 10cc (8g) and 30cc (24g) for different project needs.
- ◆ **Sample Requests:** Available for registered users to evaluate the product.

## About the Qualitek PF608 No Clean Paste Flux - Lead Free

Qualitek PF608 No Clean Paste Flux - Lead Free is a high-quality flux gel specifically formulated for lead-free applications, as well as conventional Sn/Pb alloys.

It is designed to deliver exceptional fluxing activity, promoting fast wetting action and maximum wetting spread. The clear, non-conductive, and non-tacky residue left behind ensures that no cleaning is required after use, making it a convenient solution for various soldering tasks.

**Sample Requests are available to registered users.**

## Specifications

Property	Detail
Application	ESD-protected areas, electronics mfg, cleanrooms