

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

ISOPROPANOL 90% De-Ionised Water 10%

Version 5.0

Print Date 31/10/2023

Revision date / valid from 31/10/2023

MSDS code: MIPA099

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : ISOPROPANOL <90%

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : At this time we do not yet have information on identified uses. They will be included in this safety data sheet when available.

Uses advised against : At this moment we have not identified any uses advised against

1.3. Details of the supplier of the safety data sheet

Company: Grove Sales Ltd, Unit 3 Beaver Ind. Estate, 8 Airfield Road, Christchurch
 Telephone: 01202 588900
 Email: sales@grovesales.co.uk

1.4. Emergency telephone number

Emergency telephone number : Emergency only telephone number (open 24 hours): +44 (0) 1865 407333 (N.C.E.C. Culham)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

REGULATION (EC) No 1272/2008			
Hazard class	Hazard category	Target Organs	Hazard statements
Flammable liquids	Category 2	---	H225
Serious eye damage/eye irritation	Category 2	---	H319
Specific target organ toxicity - single exposure	Category 3	---	H336

ISOPROPANOL 90% De-Ionised Water 10%

For the full text of the H-Statements mentioned in this Section, see Section 16.

Classification according to EU Directives 67/548/EEC or 1999/45/EC

Directive 67/548/EEC or 1999/45/EC	
Hazard symbol / Category of danger	Risk phrases
Highly flammable (F)	R11
Irritant (Xi)	R36
	R67



For the full text of the R-phrases mentioned in this Section, see Section 16.

Most important adverse effects

- Human Health : See section 11 for toxicological information.
- Physical and chemical hazards : See section 9 for physicochemical information.
- Potential environmental effects : See section 12 for environmental information.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

- Hazard symbols :  
- Signal word : Danger
- Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- Precautionary statements
- Prevention : P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

ISOPROPANOL 90% De-Ionised Water 10%

Response : P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Storage : P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

- propan-2-ol

2.3. Other hazards

For Results of PBT and vPvB assessment see section 12.5.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components	Amount [%]	Classification (REGULATION (EC) No 1272/2008)		Classification (67/548/EEC)
		Hazard class / Hazard category	Hazard statements	
propan-2-ol				
Index-No. : 603-117-00-0	>= 70 - <= 100	Flam. Liq.2	H225	Highly flammable; F; R11 Irritant; Xi; R36 R67
CAS-No. : 67-63-0		Eye Irrit.2	H319	
EC-No. : 200-661-7		STOT SE3	H336	
Registration : 01-2119457558-25-xxxx				

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice : Take off all contaminated clothing immediately.

If inhaled : Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position. Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

ISOPROPANOL 90% De-Ionised Water 10%

for at least 5 minutes. Consult an eye specialist immediately. Go to an ophthalmic hospital if possible.

If swallowed : Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician immediately. If a person vomits when lying on his back, place him in the recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Effects : No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2. Special hazards arising from the substance or mixture

Specific hazards during firefighting : The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixtures with air. Flash back possible over considerable distance. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Wear personal protective equipment.

Special protective equipment for firefighters :

Further advice : Cool closed containers exposed to fire with water spray. Heating will cause a pressure rise - with risk of bursting. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Remarks :

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ISOPROPANOL 90% De-Ionised Water 10%

Personal precautions : Use personal protective equipment. Keep away unprotected persons. Provide adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours or spray mist.

6.2. Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3. Methods and materials for containment and cleaning up

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4. Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on personal protective equipment.
See Section 13 for waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Keep container tightly closed. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with the skin and the eyes. Do not breathe vapours or spray mist. Emergency eye wash fountains and emergency showers should be available in the immediate vicinity.

Hygiene measures : Keep away from food, drink and animal feedingstuffs. Smoking, eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of workday. Take off all contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in an area equipped with solvent resistant flooring. Suitable materials for containers: Steel; Stainless steel

Advice on protection against fire and explosion : Combustible liquid. Keep away from sources of ignition - No smoking. The vapour may be invisible, heavier than air and spread along ground. Vapours may form explosive mixtures with air. Take measures to prevent the build up of electrostatic charge. Use only in an area containing explosion proof equipment.

Further information on storage conditions : Keep tightly closed in a dry and cool place. Keep in a well-ventilated place. Keep away from heat.

ISOPROPANOL 90% De-Ionised Water 10%

Advice on common storage : Keep away from food, drink and animal feedingstuffs. Incompatible with oxidizing agents. Do not store together with oxidizing and self-igniting products.

7.3. Specific end use(s)

Specific use(s) : No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Component:	propan-2-ol	CAS-No. 67-63-0
------------	-------------	-----------------

Derived No Effect Level (DNEL)/Derived Minimal Effect Level (DMEL)

DNEL		
Workers, Long-term - systemic effects, Skin contact	:	888 mg/kg bw/day
DNEL		
Workers, Long-term - systemic effects, Inhalation	:	500 mg/m ³
DNEL		
Consumers, Long-term - systemic effects, Skin contact	:	319 mg/kg bw/day
DNEL		
Consumers, Long-term - systemic effects, Inhalation	:	89 mg/m ³
DNEL		
Consumers, Long-term - systemic effects, Ingestion	:	26 mg/kg bw/day

Predicted No Effect Concentration (PNEC)

Fresh water	:	140.9 mg/l
Marine water	:	140.9 mg/l
Intermittent releases	:	140.9 mg/l
Sewage treatment plant (STP)	:	2251 mg/l
Sediment Related to, dry weight	:	552 mg/kg
Soil	:	28 mg/kg
Secondary poisoning Related to, food	:	160 mg/kg

ISOPROPANOL 90% De-Ionised Water 10%

Other Occupational Exposure Limit Values

EH40 WEL, Time Weighted Average (TWA):
400 ppm, 999 mg/m³

EH40 WEL, Short Term Exposure Limit (STEL):
500 ppm, 1,250 mg/m³

ELV (IE), Short Term Exposure Limit (STEL):
400 ppm

ELV (IE), Time Weighted Average (TWA):
200 ppm

8.2. Exposure controls

Appropriate engineering controls

Refer to protective measures listed in sections 7 and 8.

Personal protective equipment

Respiratory protection

Advice : In case of insufficient ventilation, wear suitable respiratory equipment.
Use respirator with appropriate filter if vapours or aerosol are released.
Recommended Filter type:A

Hand protection

Advice : The glove material has to be impermeable and resistant to the product / the substance / the preparation.
As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use.
Protective gloves should be replaced at first signs of wear.

Material : Nitrile rubber
Break through time : ≥ 8 h
Glove thickness : 0.35 mm

Material : butyl-rubber
Break through time : ≥ 8 h
Glove thickness : 0.5 mm

Material : Fluorinated rubber
Break through time : ≥ 8 h
Glove thickness : 0.4 mm

Eye protection

ISOPROPANOL 90% De-Ionised Water 10%

Advice : Tightly fitting safety goggles

Skin and body protection

Advice : Solvent resistant protective clothing

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	:	liquid
Colour	:	colourless clear
Odour	:	alcohol-like
Odour Threshold	:	no data available
pH	:	neutral
Melting point/range	:	ca. -89.5 °C
Boiling point/boiling range	:	ca. 82 °C
Flash point	:	ca. 12 °C
Evaporation rate	:	no data available
Flammability (solid, gas)	:	Formation of explosive air/vapour mixtures is possible.
Upper explosion limit	:	ca. 12 %(V)
Lower explosion limit	:	ca. 2 %(V)
Vapour pressure	:	ca. 48 hPa (20 °C)
Relative vapour density	:	ca. 2
Density	:	0.785 - 0.875 g/cm ³ (20 °C)
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	log Kow 0.05 (OECD Test Guideline 107) Literature value

ISOPROPANOL 90% De-Ionised Water 10%

Auto-ignition temperature	: ca. 425 °C
Thermal decomposition	: no data available
Viscosity, dynamic	: no data available
Explosive properties	: EU legislation: Not explosive
Explosivity	: Formation of explosive air/vapour mixtures is possible.
Oxidizing properties	: No information available.

9.2. Other information

No further information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Advice : Stable under recommended storage conditions.

10.2. Chemical stability

Advice : No decomposition if stored and applied as directed.

10.3. Possibility of hazardous reactions

Hazardous reactions : Exothermic reaction with strong acids. Incompatible with oxidizing agents.

10.4. Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Thermal decomposition : no data available

10.5. Incompatible materials

Materials to avoid : Strong acids and oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products : Under fire conditions: Carbon oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Oral

ISOPROPANOL 90% De-Ionised Water 10%

Please find this information in the listing of the component/components below in the MSDS.

Inhalation

Please find this information in the listing of the component/components below in the MSDS.

Dermal

Please find this information in the listing of the component/components below in the MSDS.

Irritation

Skin

Result : Please find this information in the listing of the component/components below in the MSDS.

Eyes

Result : Please find this information in the listing of the component/components below in the MSDS.

Sensitisation

Result : Please find this information in the listing of the component/components below in the MSDS.

CMR effects

CMR Properties

Carcinogenicity : Please find this information in the listing of the component/components below in the MSDS.

Mutagenicity : Please find this information in the listing of the component/components below in the MSDS.

Teratogenicity : Please find this information in the listing of the component/components below in the MSDS.

Reproductive toxicity : Please find this information in the listing of the component/components below in the MSDS.

Specific Target Organ Toxicity

Single exposure

ISOPROPANOL 90% De-Ionised Water 10%

Inhalation : May cause drowsiness or dizziness.

Repeated exposure

remark : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Other toxic properties

Repeated dose toxicity

no data available

Aspiration hazard

No aspiration toxicity classification

Further information

Other relevant toxicity information : Prolonged skin contact may defat the skin and produce dermatitis. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Risk of product entering the lungs on vomiting after ingestion. Liver injury may occur.

Component: **propan-2-ol** **CAS-No. 67-63-0**

Acute toxicity

Oral

LD50 : 5840 mg/kg (Rat) (OECD Test Guideline 401)

Inhalation

LC50 : > 25 mg/l (Rat; 6 h; vapour) (OECD Test Guideline 403)

Dermal

LD50 Dermal : 13900 mg/kg (Rabbit) (OECD Test Guideline 402)

Irritation

Skin

Result : No skin irritation (OECD Test Guideline 404)
Decreases the skin which may cause dry and rough. Prolonged or repeated skin contact may result in dermatitis.

Eyes

ISOPROPANOL 90% De-Ionised Water 10%

Result : Eye irritation (OECD Test Guideline 405)
Splashes in eyes may cause strong pain. Vapour acts irritant.

Sensitisation

Result : Does not cause skin sensitisation. (OECD Test Guideline 406)

CMR effects

CMR Properties

Carcinogenicity : Based on available data, the classification criteria are not met.

Mutagenicity : In vitro tests did not show mutagenic effects
In vivo tests did not show mutagenic effects

Teratogenicity : No effects on or via lactation

Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity

Single exposure

Inhalation : Target Organs: Central nervous system
May cause drowsiness or dizziness.

Repeated exposure

remark : Oral and inhalation repeated exposure studies demonstrated target organ effects in male rats (kidney) and male and female mice (thyroid) by mechanisms of action that are not relevant to humans

Other toxic properties

Aspiration hazard

Aspiration hazard if swallowed - can enter lungs and cause damage.
Aspiration may cause pulmonary oedema and pneumonitis.

SECTION 12: Ecological information

12.1. Toxicity

Component: propan-2-ol **CAS-No.** 67-63-0

Acute toxicity

Fish

ISOPROPANOL 90% De-Ionised Water 10%

LC50 : 9640 mg/l (Pimephales promelas; 96 h)

Toxicity to daphnia and other aquatic invertebrates

LC50 : 9714 mg/l (Daphnia magna; 24 h)

algae

EC50 : > 100 mg/l (Scenedesmus subspicatus; 72 h)

Bacteria

EC50 : > 100 mg/l (Bacteria)
no harming action

12.2. Persistence and degradability

Component:	propan-2-ol	CAS-No. 67-63-0
-------------------	--------------------	------------------------

Persistence and degradability

Persistence

Result : no data available

Biodegradability

Result : 53 % (Exposure Time: 5 d)
Readily biodegradable.

12.3. Bioaccumulative potential

Component:	propan-2-ol	CAS-No. 67-63-0
-------------------	--------------------	------------------------

Bioaccumulation

Result : Bioaccumulation is not expected.

12.4. Mobility in soil

Component:	propan-2-ol	CAS-No. 67-63-0
-------------------	--------------------	------------------------

Mobility

: The product is mobile in water environment.

12.5. Results of PBT and vPvB assessment

ISOPROPANOL 90% De-Ionised Water 10%

Component: propan-2-ol CAS-No. 67-63-0

Results of PBT and vPvB assessment

Result : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).

12.6. Other adverse effects

Additional ecological information

Result : Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Product : Disposal together with normal waste is not allowed. Special disposal required according to local regulations. Do not let product enter drains. Contact waste disposal services.
- Contaminated packaging : Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleaned are to be disposed of in the same manner as the product. Do not burn, or use a cutting torch on, the empty drum. Risk of explosion.
- European Waste Catalogue Number : No waste code according to the European Waste Catalogue can be assigned for this product, as the intended use dictates the assignment. The waste code is established in consultation with the regional waste disposer.

SECTION 14: Transport information

14.1. UN number

1219

14.2. UN proper shipping name

ADR : ISOPROPANOL
RID : ISOPROPANOL
IMDG : ISOPROPANOL

14.3. Transport hazard class(es)

ADR-Class : 3
(Labels; Classification Code; Hazard identification No; Tunnel restriction code) 3; F1; 33; (D/E)

ISOPROPANOL 70-100%

RID-Class : 3
(Labels; Classification Code; Hazard identification No) 3; F1; 33
IMDG-Class : 3
(Labels; EmS) 3; F-E, S-D

14.4. Packaging group

ADR : II
RID : II
IMDG : II

14.5. Environmental hazards

Environmentally hazardous according to ADR : no
Environmentally hazardous according to RID : no
Marine Pollutant according to IMDG-Code : no

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : Occupational restrictions: Take note of Dir 92/85/EEC on the safety and health of pregnant workers at work and of Dir 94/33/EC on the protection of young people at work.

Component:	propan-2-ol	CAS-No. 67-63-0
-------------------	--------------------	------------------------

EU. REACH, Annex XVII, : Point Nos.: , 40; Listed
Marketing and Use
Restrictions (Regulation
1907/2006/EC)

EU. Regulation No : EC Number: , 200-661-7; Listed
1451/2007 [Biocides],
Annex I, Active
substances identified as
existing (OJ (L 325)

EU. Directive 96/82/EC : Threshold quantities established for the application of Article 9:
(Seveso II) 50,000 tonnes; Part 2: Categories of substances and
preparations not specifically named in Part 1
Threshold quantities established for the application of Articles 6
and 7: 5,000 tonnes; Part 2: Categories of substances and

ISOPROPANOL 70-100%

preparations not specifically named in Part 1

WGK (DE) : slightly water endangering: 135; Classification source is Annex 2.

Notification status propan-2-ol:

Regulatory List	Notification	Notification number
AICS	YES	
DSL	YES	
INV (CN)	YES	
ENCS (JP)	YES	(2)-207
JEX (JP)	YES	(2)-207
ISHL (JP)	YES	(2)-207
ISHL (JP)	YES	2-(8)-319
NZ CLSC	YES	
TSCA	YES	
EINECS	YES	200-661-7
KECI (KR)	YES	KE-29363
PICCS (PH)	YES	
IECSC	YES	

15.2. Chemical Safety Assessment

no data available

SECTION 16: Other information

Full text of R-phrases referred to under sections 2 and 3.

R11	Highly flammable.
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further information

Key literature references : Supplier information and data from the "Database of registered substances" of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Other information : The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material

ISOPROPANOL 70-100%

or in any process, unless specified in the text

|| Indicates updated section.

ISOPROPANOL 70-100%

No.	Short title	Main User Group (SU)	Sector of Use (SU)	Product Category (PC)	Process Category (PROC)	Environmental Release Category (ERC)	Article Category (AC)	Specified
1	Manufacture of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 15	1, 4	NA	ES001
2	Use as an intermediate	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 15	6a	NA	ES003
3	Distribution of substance	3	8, 9	NA	1, 2, 3, 4, 8a, 8b, 9, 15	1, 2, 3, 4, 5, 6a, 6b, 6c, 6d, 7	NA	ES005
4	Formulation & (re)packing of substances and mixtures	3	10	NA	1, 2, 3, 4, 5, 8a, 8b, 9, 14, 15	2	NA	ES007
5	Use in Cleaning Agents	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 10, 13	4	NA	ES011
6	Use in Cleaning Agents	21	NA	3, 4, 8, 9a, 24, 35, 38	NA	8a, 8d	NA	ES338
7	Use in Cleaning Agents	22	NA	NA	1, 2, 3, 4, 8a, 8b, 10, 11, 13	8a, 8d	NA	ES041
8	Use as a fuel	3	NA	NA	1, 2, 3, 8a, 8b, 16	7	NA	ES023
9	Use as a fuel	21	NA	13	NA	9a, 9b	NA	ES440
10	Use as a fuel	22	NA	NA	1, 2, 3, 8a, 8b, 16	9a, 9b	NA	ES051
11	Use as lubricants	3	NA	NA	1, 2, 3, 4, 7, 8a, 8b, 9, 10, 13, 17, 18	4, 7	NA	ES015
12	Use as lubricants	21	NA	1, 24, 31	NA	8a, 8d, 9a, 9b	NA	ES427
13	Use as lubricants	22	NA	NA	1, 2, 3, 4, 8a, 8b, 9, 10, 11, 13, 17, 18, 20	8a, 9a, 9b, 8d	NA	ES036
14	Use as Functional Fluids	3	NA	NA	1, 2, 4, 8a, 8b, 9	7	NA	ES025
15	Use as Functional Fluids	21	NA	16, 17	NA	9a, 9b	NA	ES449
16	Use as Functional Fluids	22	NA	NA	1, 2, 3, 8a, 9, 20	9a, 9b	NA	ES053
17	Use in laboratories	3	NA	NA	10, 15	2, 4	NA	ES027
18	Use in laboratories	22	NA	NA	10, 15	8a	NA	ES061
19	Use in metal working fluids / rolling oils	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 17	4	NA	ES017
20	Use in metal working fluids / rolling oils	22	NA	NA	1, 2, 3, 8a, 8b, 9, 10, 11, 13, 17	8a, 8d	NA	ES045
21	Use in de-icing and anti-icing applications	21	NA	4	NA	8d	NA	ES453
22	Use in de-icing and anti-icing applications	22	NA	NA	8b, 11	8d	NA	ES055

ISOPROPANOL 70-100%

23	Use as water treatment chemicals	3	NA	NA	1, 2, 3, 4, 8a, 8b, 13	3, 4	NA	ES033
24	Use as water treatment chemicals	21	NA	36, 37	NA	8f	NA	ES459
25	Use as water treatment chemicals	22	NA	NA	1, 3, 4, 8a, 8b, 13	8f	NA	ES071
26	Other consumer uses	21	NA	28, 39	NA	8a, 8d	NA	ES457
27	Uses in coatings	3	NA	NA	1, 2, 3, 4, 5, 7, 8a, 8b, 9, 10, 13, 14, 15	4	NA	ES009
28	Uses in coatings	21	NA	1, 4, 8, 9a, 9b, 9c, 15, 18, 23, 24, 31, 34	NA	8a, 8d	NA	ES073
29	Uses in coatings	22	NA	NA	1, 2, 3, 4, 5, 8a, 8b, 10, 11, 13, 15, 19	8a, 8d	NA	ES039
30	Use as binders and release agents	3	NA	NA	1, 2, 3, 4, 6, 7, 8b, 10, 14	4	NA	ES021
31	Use as binders and release agents	22	NA	NA	1, 2, 3, 4, 6, 8b, 10, 11, 14	8a, 8d	NA	ES047
32	Use in agrochemicals	21	NA	12, 27	NA	8a, 8d	NA	ES438
33	Use in agrochemicals	22	NA	NA	1, 2, 4, 8a, 8b, 11, 13	8a, 8d	NA	ES049

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 1: Manufacture of substance

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Handle substance within a closed system.(PROC4)
	Bulk transfers (open systems)	Handle substance within a closed system.(PROC8b)
	Bulk transfers (closed systems)	Ensure material transfers are under containment or extract ventilation. Clear transfer lines prior to de-coupling.(PROC8b)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Clear spills immediately.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC2)
Conditions and measures related to personal protection, hygiene	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

and health evaluation

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 2: Use as an intermediate

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental Release Categories	ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

2.1 Contributing scenario controlling environmental exposure for: ERC6a

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Handle substance within a closed system.(PROC4)
	Bulk transfers (open systems)	Handle substance within a closed system.(PROC8b)
	Bulk transfers (closed systems)	Ensure material transfers are under containment or extract ventilation.(PROC8b)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Clear spills immediately.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

ISOPROPANOL 70-100%

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 3: Distribution of substance

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU8: Manufacture of bulk, large scale chemicals (including petroleum products) SU9: Manufacture of fine chemicals
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC15: Use as laboratory reagent
Environmental Release Categories	ERC1: Manufacture of substances ERC2: Formulation of preparations ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates) ERC6b: Industrial use of reactive processing aids ERC6c: Industrial use of monomers for manufacture of thermoplastics ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	General exposures (open systems)	Clear transfer lines prior to de-coupling.(PROC4)
	Process sampling	Avoid dip sampling.(PROC3)
	Bulk transfers (open systems)	Clear transfer lines prior to de-coupling.(PROC8b)

ISOPROPANOL 70-100%

	Bulk transfers (closed systems)	Clear transfer lines prior to de-coupling.(PROC8b)
	Drum and small package filling	Clear spills immediately. Put lids on containers immediately after use.(PROC9)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance. Apply vessel entry procedures including use of forced supplied air.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 4: Formulation & (re)packing of substances and mixtures

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sectors of end-use	SU 10: Formulation
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC2: Formulation of preparations

2.1 Contributing scenario controlling environmental exposure for: ERC2

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Process sampling	Avoid dip sampling.(PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Drum and small package filling	Put lids on containers immediately after use.(PROC9)
	Equipment cleaning and maintenance	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC2)
Conditions and measures related to personal protection, hygiene	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

and health evaluation

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 5: Use in Cleaning Agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC7: Industrial spraying PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8a)
	Filling / preparation of equipment from drums or containers	Clear transfer lines prior to de-coupling.(PROC8b)
	Cleaning with high pressure washers	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC7)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ISOPROPANOL 70-100%

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 6: Use in Cleaning Agents

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC3: Air care products PC4: Anti-freeze and de-icing products PC8: Biocidal products PC9a: Coatings and paints, thinners, paint removers PC24: Lubricants, greases, release products PC35: Washing and cleaning products (including solvent based products) PC38: Welding and soldering products (with flux coatings or flux cores), flux products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC3: Aircare, instant action (aerosol sprays)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	4 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC3: Aircare, continuous action (solid & liquid)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.48 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per	480 min

ISOPROPANOL 70-100%

	event	
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.7 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.4 Contributing scenario controlling consumer exposure for: PC4: Washing car window		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.5 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
R56871 / Version 5.0		
31/103		
EN		

ISOPROPANOL 70-100%

2.6 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC8: Laundry and dish washing products

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	15 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	30 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.8 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g

ISOPROPANOL 70-100%

Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.9 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.10 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint

Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient	

ISOPROPANOL 70-100%

temperatures.		
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.11 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.12 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-, wall paper-, sealant-remover)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.13 Contributing scenario controlling consumer exposure for: PC24: Liquids		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
R56871 / Version 5.0		
34/103		
EN		

ISOPROPANOL 70-100%

	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.14 Contributing scenario controlling consumer exposure for: PC24: Pastes

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.15 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min

ISOPROPANOL 70-100%

Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.16 Contributing scenario controlling consumer exposure for: PC35: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.17 Contributing scenario controlling consumer exposure for: PC35: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 15%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
R56871 / Version 5.0		
36/103		
EN		

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

2.18 Contributing scenario controlling consumer exposure for: PC38

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	12 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 7: Use in Cleaning Agents

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Cleaning with high pressure washers Spraying Indoor.	Provide a good standard of controlled ventilation (10 to 15 air changes per hour)(PROC11)
	Cleaning with high pressure washers Spraying Outdoor.	Limit the substance content in the mixture to 1 %. or Avoid carrying out operation for more than 15 minutes. Ensure operation is undertaken outdoors.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 8: Use as a fuel

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC8b)
	Drum/batch transfers	Avoid spillage when withdrawing pump. Use drum pumps or carefully pour from container.(PROC8b)
	General exposures (open systems) (closed systems)	Handle substance within a closed system.(PROC1, PROC2)
	Equipment cleaning and maintenance	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Drain down system prior to equipment break-in or maintenance.(PROC8a)
	Vessel and container cleaning	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 9: Use as a fuel

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC13: Fuels
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

2.2 Contributing scenario controlling consumer exposure for: PC13: Liquid: Automotive Refuelling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	37500 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	3 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use.	
	Room size	100 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC13: Liquid: Scooter Refuelling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	3750 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use.	
	Room size	100 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

2.4 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Use

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 420 cm ²
Other given operational conditions affecting consumers exposure	Outdoor use.	
	Room size	100 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.5 Contributing scenario controlling consumer exposure for: PC13: Liquid: Garden Equipment - Refueling

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 420 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.6 Contributing scenario controlling consumer exposure for: PC13: Liquid: home space heater fuel

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
-------------------------	---	---

ISOPROPANOL 70-100%

	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	750 g
Frequency and duration of use	Frequency of use	26 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC13: Liquid: Lamp oil

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	100 g
Frequency and duration of use	Frequency of use	52 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	0.6 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 210 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ISOPROPANOL 70-100%

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 10: Use as a fuel

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC16: Using material as fuel sources, limited exposure to unburned product to be expected
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC8b)
	Drum/batch transfers	Avoid spillage when withdrawing pump.(PROC8b)
	refuelling aircraft	Avoid spillage when withdrawing pump.(PROC8a)
	General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	General exposures (open systems) (closed systems)	Handle substance within a closed system.(PROC16)
	Equipment cleaning and maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Vessel and container cleaning	Apply vessel entry procedures including use of forced supplied air. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
Storage	Store substance within a closed system.(PROC1, PROC2)	
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

ISOPROPANOL 70-100%

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 11: Use as lubricants

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p> <p>PROC18: Greasing at high energy conditions</p>
Environmental Release Categories	<p>ERC4: Industrial use of processing aids in processes and products, not becoming part of articles</p> <p>ERC7: Industrial use of substances in closed systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Operation and lubrication of high energy open equipment	Provide extract ventilation to points where emissions occur. Restrict area of openings to equipment.(PROC17, PROC18)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible. Clear transfer lines prior to de-coupling.(PROC7)
	Maintenance (of larger plant items) and machine set up	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

ISOPROPANOL 70-100%

		Automate activity where possible.(PROC8b)
	Maintenance of small items	Avoid manual contact with wet work pieces. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Storage	Store substance within a closed system. Avoid dip sampling.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Bulk transfers	Wear suitable gloves tested to EN374.(PROC8b)
		Wear suitable gloves tested to EN374.(PROC8b)
		Use suitable eye protection.
		Avoid direct eye contact with product, also via contamination on hands.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information on the assessment method, see: <http://www.ecetoc.org/tra> Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 12: Use as lubricants

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC24: Lubricants, greases, release products PC31: Polishes and wax blends
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	6390 g
Frequency and duration of use	Frequency of use	1 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 110 cm ²

ISOPROPANOL 70-100%

Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85.05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.6 Contributing scenario controlling consumer exposure for: PC24: Liquids		
Product characteristics	Concentration of the Substance in	Covers percentage substance in the product up to 100 % (unless stated differently).
R56871 / Version 5.0		
51/103		EN

ISOPROPANOL 70-100%

	Mixture/Article	
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.7 Contributing scenario controlling consumer exposure for: PC24: Pastes

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.8 Contributing scenario controlling consumer exposure for: PC24: Sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min

ISOPROPANOL 70-100%

	event	
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.9 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.10 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified
R56871 / Version 5.0		
53/103		EN

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 13: Use as lubricants

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p> <p>PROC18: Greasing at high energy conditions</p> <p>PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC9a: Wide dispersive indoor use of substances in closed systems</p> <p>ERC9b: Wide dispersive outdoor use of substances in closed systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d, ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	4 hours/day (PROC8a, PROC11, PROC17, PROC18)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system. (PROC1, PROC2, PROC3)
	Operation and lubrication of high energy open equipment Indoor.	Restrict area of openings to equipment. Provide extraction ventilation at points where emissions occur. (PROC17, PROC18)
	Operation and lubrication of high energy open equipment Outdoor.	Ensure operation is undertaken outdoors. (PROC17)
	Maintenance (of larger plant items) and machine	Provide extract ventilation to emission points when contact with warm (>50°C) product is

ISOPROPANOL 70-100%

	set up	likely.(PROC8b)
	Maintenance of small items	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.(PROC11)
	Treatment by dipping and pouring	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Allow time for product to drain from workpiece.(PROC13)
	Treatment by dipping and pouring	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Allow time for product to drain from workpiece.(PROC13)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Maintenance of small items	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC8a)
	Spraying	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)
	Treatment by dipping and pouring	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC13)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 14: Use as Functional Fluids

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
Environmental Release Categories	ERC7: Industrial use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC7

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC9

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers (closed systems)	Transfer via enclosed lines. Clear transfer lines prior to de-coupling.(PROC1, PROC2)
	Filling / preparation of equipment from drums or containers	Carefully pour from containers.(PROC8a)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

ISOPROPANOL 70-100%

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 15: Use as Functional Fluids

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC16: Heat transfer fluids PC17: Hydraulic fluids
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC16, PC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 16: Use as Functional Fluids

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems
Environmental Release Categories	ERC9a: Wide dispersive indoor use of substances in closed systems ERC9b: Wide dispersive outdoor use of substances in closed systems

2.1 Contributing scenario controlling environmental exposure for: ERC9a, ERC9b

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Transfer from/pouring from containers	Avoid spillage when withdrawing pump.(PROC9)
	Remanufacture of reject articles	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC9)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

ISOPROPANOL 70-100%

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 17: Use in laboratories

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC2: Formulation of preparations ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC15)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Laboratory activities	Automate activity where possible. Restrict area of openings to equipment. Handle substance within a closed system. Clear spills immediately. Remotely vent displaced vapours. Use dedicated equipment.(PROC15)
	cleaning	Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Automate activity where possible. Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC10)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may

ISOPROPANOL 70-100%

be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 18: Use in laboratories

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC10: Roller application or brushing PROC15: Use as laboratory reagent
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC15)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Laboratory activities	Handle substance within a closed system. Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours. Use dedicated equipment. Restrict area of openings to equipment. Allow time for product to drain from workpiece. Automate activity where possible.(PROC15)
	cleaning	Automate activity where possible. Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC10)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 19: Use in metal working fluids / rolling oils

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC17: Lubrication at high energy conditions and in partly open process</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling. Clear spills immediately. Remotely vent displaced vapours.(PROC8b)
	Process sampling	Use dedicated equipment.(PROC8b)
	Metal machining operations	Restrict area of openings to equipment.(PROC17)
	Treatment by dipping and pouring	Allow time for product to drain from workpiece. Automate activity where possible.(PROC13)
	Spraying	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC7)
	Rolling, Brushing Manual	Avoid splashing.(PROC10)

ISOPROPANOL 70-100%

	Semi-automated metal rolling/forming	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC17)
	Equipment cleaning and maintenance Dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8b)
	Equipment cleaning and maintenance Non-dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 20: Use in metal working fluids / rolling oils

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring PROC17: Lubrication at high energy conditions and in partly open process
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 1 hours/day(PROC8a)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1, PROC2, PROC3)
	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Filling / preparation of equipment from drums or containers Dedicated facility	Clear transfer lines prior to de-coupling.(PROC8b)
	Metal machining operations	Provide enhanced general ventilation by mechanical means.(PROC17)
	Spraying	Provide enhanced general ventilation by mechanical means.(PROC11)
	Treatment by dipping and pouring	Allow time for product to drain from workpiece.(PROC13)
	Equipment cleaning and maintenance Non-dedicated facility	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
Equipment cleaning and maintenance	Clear transfer lines prior to de-coupling.(PROC8b)	

ISOPROPANOL 70-100%

	Dedicated facility	
	Storage	Handle substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Spraying	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 21: Use in de-icing and anti-icing applications

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC4: Anti-freeze and de-icing products
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC4: Washing car window

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 1 %.
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g.	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

ISOPROPANOL 70-100%

behavioural advice, personal protection and hygiene)

2.4 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 40%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 22: Use in de-icing and anti-icing applications

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC11: Non industrial spraying
Environmental Release Categories	ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC8b, PROC11

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 1 hours/day(PROC11)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Spraying/fogging by machine application	Ensure operation is undertaken outdoors.(PROC11)
Organisational measures to prevent /limit releases, dispersion and exposure	Spraying/fogging by machine application	Stay upwind/ keep distance from source.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

ISOPROPANOL 70-100%

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 23: Use as water treatment chemicals

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC3: Formulation in materials ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC3, ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Bulk transfers	Handle substance within a closed system. Clear transfer lines prior to de-coupling.(PROC2)
	Drum/batch transfers	Avoid spillage when withdrawing pump.(PROC8b)
	General exposures (open systems)	Restrict area of openings to equipment.(PROC4)
	Pouring from small containers	Use drum pumps or carefully pour from container.(PROC13)
	Batch process	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 24: Use as water treatment chemicals

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC36: Water softeners PC37: Water treatment chemicals
Environmental Release Categories	ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

2.1 Contributing scenario controlling environmental exposure for: ERC8f

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC36

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	10 g
	Amount used per event (oral exposure)	0.000015 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC37

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	10 g
	Amount used per event (oral exposure)	0.000154 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 6600 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related	Consumer Measures	No specific risk management measure identified

ISOPROPANOL 70-100%

to protection of consumer (e.g. behavioural advice, personal protection and hygiene)

beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 25: Use as water treatment chemicals

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8f: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

2.1 Contributing scenario controlling environmental exposure for: ERC8f

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC4, PROC8a, PROC8b, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Drum/batch transfers	Avoid spillage when withdrawing pump. Clear transfer lines prior to de-coupling. Use drum pumps or carefully pour from container.(PROC8b)
	General exposures (open systems)	Restrict area of openings to equipment.(PROC4)
	Pouring from small containers	Carefully pour from containers. Avoid spillage when withdrawing pump.(PROC13)
	Equipment maintenance	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Storage	Store substance within a closed system.(PROC1)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

ISOPROPANOL 70-100%

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 26: Other consumer uses

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC28: Perfumes, fragrances PC39: Cosmetics, personal care products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems
Activity	Note: this Exposure Scenario is only relevant for an appropriated use according to the quality grade of the substance delivered

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC28, PC39

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 27: Uses in coatings

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC7: Industrial spraying</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC10: Roller application or brushing</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p> <p>PROC15: Use as laboratory reagent</p>
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	General exposures (closed systems) with sample collection Use in contained systems	Handle substance within a closed system.(PROC2)
	Film formation - force drying (50-100°C). Stoving (>100°C). UV/EB radiation curing	Handle substance within a closed system.(PROC2)
	Mixing operations (closed systems) General exposures (closed systems)	Handle substance within a closed system.(PROC3)
	Spraying	Carry out in a vented booth provided with laminar

ISOPROPANOL 70-100%

	(automatic/robotic)	airflow.(PROC7)
	Manual Spraying	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour).(PROC7)
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8a)
	Material transfers	Clear transfer lines prior to de-coupling.(PROC8b)
	Dipping, immersion and pouring	Avoid manual contact with wet work pieces.(PROC13)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection.	
	Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
For further information on the assessment method, see: <http://www.ecetoc.org/tra>
Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 28: Uses in coatings

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC1: Adhesives, sealants PC4: Anti-freeze and de-icing products PC8: Biocidal products PC9a: Coatings and paints, thinners, paint removers PC9b: Fillers, putties, plasters, modelling clay PC9c: Finger paints PC15: Non-metal-surface treatment products PC18: Ink and toners PC23: Leather tanning, dye, finishing, impregnation and care products PC24: Lubricants, greases, release products PC31: Polishes and wax blends PC34: Textile dyes, finishing and impregnating products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC1: Glues, hobby use

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	9 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.3 Contributing scenario controlling consumer exposure for: PC1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	6390 g

ISOPROPANOL 70-100%

Frequency and duration of use	Frequency of use	1 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 110 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.4 Contributing scenario controlling consumer exposure for: PC1: Glue from spray

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85.05 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.5 Contributing scenario controlling consumer exposure for: PC1: Sealants

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 30%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	75 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	

ISOPROPANOL 70-100%

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.6 Contributing scenario controlling consumer exposure for: PC4: Washing car window		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.5 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	1.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.7 Contributing scenario controlling consumer exposure for: PC4: Pouring into radiator		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2000 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.8 Contributing scenario controlling consumer exposure for: PC4: Lock de-icer		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid

ISOPROPANOL 70-100%

	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	4 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	15 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 214.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.9 Contributing scenario controlling consumer exposure for: PC8: Cleaners, liquids

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	27 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.10 Contributing scenario controlling consumer exposure for: PC8: Cleaners, trigger sprays

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 15%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	128 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428 cm ²

ISOPROPANOL 70-100%

Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.11 Contributing scenario controlling consumer exposure for: PC9a: Solvent rich, high solid, water borne paint, PC15: Solvent rich, high solid, water borne paint		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers concentrations up to 27,5%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	744 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.12 Contributing scenario controlling consumer exposure for: PC9a: Aerosol spray can, PC15: Aerosol spray can		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	215 g
Frequency and duration of use	Frequency of use	2 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.13 Contributing scenario controlling consumer exposure for: PC9a: Removers (paint-, glue-,		
R56871 / Version 5.0		
87/103		
EN		

ISOPROPANOL 70-100%

wall paper-, sealant-remover), PC15: Removers (paint-, glue-, wall paper-, sealant remover)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	491 g
Frequency and duration of use	Frequency of use	3 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.14 Contributing scenario controlling consumer exposure for: PC9b: Fillers and putty

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	85 g
Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	240 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 35.73 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.15 Contributing scenario controlling consumer exposure for: PC9b: Plasters and floor equalizers

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 2%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	13800 g

ISOPROPANOL 70-100%

Frequency and duration of use	Frequency of use	12 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	120 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.16 Contributing scenario controlling consumer exposure for: PC9b: Modelling clay

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	1 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.17 Contributing scenario controlling consumer exposure for: PC9c

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	1.35 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 254.4 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	

ISOPROPANOL 70-100%

Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	Avoid using at a product concentration greater than 15 %
--	-------------------	--

2.18 Contributing scenario controlling consumer exposure for: PC18

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	40 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	132 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 71.40 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.19 Contributing scenario controlling consumer exposure for: PC23: Polishes, wax/cream (floor, furniture, shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m3
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.20 Contributing scenario controlling consumer exposure for: PC23: Polishes, spray (furniture, shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
-------------------------	---	--

ISOPROPANOL 70-100%

	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	56 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.21 Contributing scenario controlling consumer exposure for: PC24: Liquids		
Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	2200 g
Frequency and duration of use	Frequency of use	4 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	34 m ³
		Covers use under typical household ventilation., Covers use at ambient temperatures., Covers use in a one car garage (34m ³) under typical ventilation.
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.22 Contributing scenario controlling consumer exposure for: PC24: Pastes		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 20%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	34 g
Frequency and duration of use	Frequency of use	10 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	360 min
R56871 / Version 5.0		
91/103		
EN		

ISOPROPANOL 70-100%

Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 468 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.23 Contributing scenario controlling consumer exposure for: PC24: Sprays		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	73 g
Frequency and duration of use	Frequency of use	6 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	10.2 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 428.75 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
2.24 Contributing scenario controlling consumer exposure for: PC31: Polishes, wax / cream (floor, furniture, shoes)		
Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	142 g
Frequency and duration of use	Frequency of use	29 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	73.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.
R56871 / Version 5.0		
92/103		
EN		

ISOPROPANOL 70-100%

2.25 Contributing scenario controlling consumer exposure for: PC31: Polishes, spray (furniture, shoes)

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	35 g
Frequency and duration of use	Frequency of use	8 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	19.8 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 430 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

2.26 Contributing scenario controlling consumer exposure for: PC34

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 10%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	115 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
	Exposure duration per event	60 min
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

ISOPROPANOL 70-100%

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 29: Uses in coatings

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC13: Treatment of articles by dipping and pouring</p> <p>PROC15: Use as laboratory reagent</p> <p>PROC19: Hand-mixing with intimate contact and only PPE available</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	General exposures (closed systems)	Handle substance within a closed system.(PROC1)
	Filling / preparation of equipment from drums or containers	Handle substance within a closed system.(PROC2)
	General exposures (closed systems) Use in contained systems	Handle substance within a closed system.(PROC2)
	Manual Spraying Indoor.	Carry out in a vented booth or extracted enclosure.(PROC11)
	Manual Spraying Outdoor.	Ensure operation is undertaken outdoors.(PROC11)
	Dipping, immersion and pouring Indoor.	Avoid manual contact with wet work pieces. Clear up spills immediately and dispose of waste safely.(PROC13)

ISOPROPANOL 70-100%

	Dipping, immersion and pouring Outdoor.	Avoid manual contact with wet work pieces. Clear up spills immediately and dispose of waste safely.(PROC13)
	Hand application - finger paints, pastels, adhesives Indoor.	Ensure doors and windows are opened.(PROC19)
Conditions and measures related to personal protection, hygiene and health evaluation	Manual Spraying Outdoor.	Wear a respirator conforming to EN140 with Type A filter or better.(PROC11)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 30: Use as binders and release agents

Main User Groups	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC6: Calendering operations PROC7: Industrial spraying PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC10: Roller application or brushing PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation
Environmental Release Categories	ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

2.1 Contributing scenario controlling environmental exposure for: ERC4

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8b, PROC10, PROC14

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Technical conditions and measures to control dispersion from source towards the worker	Material transfers	Clear transfer lines prior to de-coupling.(PROC1, PROC2, PROC3)
	Casting operations (open systems)	Provide extraction ventilation at points where emissions occur.(PROC6)
	Spraying Machine	Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Automate activity where possible.(PROC7)
	Spraying Manual	Carry out in a vented booth or extracted enclosure.(PROC7)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

ISOPROPANOL 70-100%

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 31: Use as binders and release agents

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	<p>PROC1: Use in closed process, no likelihood of exposure</p> <p>PROC2: Use in closed, continuous process with occasional controlled exposure</p> <p>PROC3: Use in closed batch process (synthesis or formulation)</p> <p>PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises</p> <p>PROC6: Calendaring operations</p> <p>PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</p> <p>PROC10: Roller application or brushing</p> <p>PROC11: Non industrial spraying</p> <p>PROC14: Production of preparations or articles by tableting, compression, extrusion, pelletisation</p>
Environmental Release Categories	<p>ERC8a: Wide dispersive indoor use of processing aids in open systems</p> <p>ERC8d: Wide dispersive outdoor use of processing aids in open systems</p>

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC6, PROC8b, PROC10, PROC11, PROC14, PROC1, PROC2, PROC3, PROC4

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Other operational conditions affecting workers exposure	Limit the substance content in the mixture to 25 %.(PROC6)	
Technical conditions and measures to control dispersion from source towards the worker	Material transfers (closed systems)	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC1, PROC2, PROC3)
	Casting operations (open systems)	Provide extraction ventilation at points where emissions occur.(PROC6)
	Spraying Machine	Minimise exposure by extracted full enclosure for the operation or equipment.(PROC11)
	Spraying Manual	Carry out in a vented booth or extracted enclosure.(PROC11)
	Batch process	Store substance within a closed system.(PROC1, PROC2)
Organisational measures to prevent /limit releases, dispersion and exposure	Spraying Machine	Segregate the activity away from other operations.(PROC11)
	Spraying Manual	Segregate the activity away from other operations.(PROC11)
Conditions and measures related to personal protection, hygiene and health evaluation	Spraying Manual	Wear a respirator conforming to EN140 with Type A/P2 filter or better.(PROC11)
	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

ISOPROPANOL 70-100%

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 32: Use in agrochemicals

Main User Groups	SU 21: Consumer uses: Private households (= general public = consumers)
Chemical product category	PC12: Fertilizers PC27: Plant protection products
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling consumer exposure for: PC12, PC27

Product characteristics	Concentration of the Substance in Mixture/Article	Concentration of substance in product : 0% - 50%
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Amount used	Amount used per event	0.3 g
Frequency and duration of use	Frequency of use	365 days/year
	Frequency of use	1 Times per day
Human factors not influenced by risk management	Exposed skin areas	Covers skin contact area up to 857.5 cm ²
Other given operational conditions affecting consumers exposure	Room size	20 m ³
	Covers use under typical household ventilation., Covers use at ambient temperatures.	
Conditions and measures related to protection of consumer (e.g. behavioural advice, personal protection and hygiene)	Consumer Measures	No specific risk management measure identified beyond those operational conditions stated.

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

Consumers

The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated. Predicted exposures are not expected to exceed the applicable exposure limits when the operational conditions/risk management measures given in section 2 are implemented.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ISOPROPANOL 70-100%

1. Short title of Exposure Scenario 33: Use in agrochemicals

Main User Groups	SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Process categories	PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC11: Non industrial spraying PROC13: Treatment of articles by dipping and pouring
Environmental Release Categories	ERC8a: Wide dispersive indoor use of processing aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open systems

2.1 Contributing scenario controlling environmental exposure for: ERC8a, ERC8d

As no environmental hazard was identified no environmental related exposure assessment and risk characterization was performed.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13

Product characteristics	Concentration of the Substance in Mixture/Article	Covers percentage substance in the product up to 100 % (unless stated differently).
	Physical Form (at time of use)	liquid
	Vapour pressure	0.5 - 10 kPa
Frequency and duration of use	Frequency of use	8 hours/day
	Frequency of use	< 4 hours/day(PROC11)
Human factors not influenced by risk management	Assumes use at not more than 20°C above ambient temperature.	
Other operational conditions affecting workers exposure	Limit the substance content in the mixture to 25 %.(PROC11)	
Technical conditions and measures to control dispersion from source towards the worker	Spraying/fogging by machine application	Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.(PROC11)
	Operation of equipment containing engine oils and similar	Retain drain downs in sealed storage pending disposal or for subsequent recycle.(PROC8a)
	Disposal of wastes	Clear up spills immediately and dispose of waste safely.(PROC8a)
	Storage	Store substance within a closed system.(PROC1, PROC2)
Conditions and measures related to personal protection, hygiene and health evaluation	Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.	

3. Exposure estimation and reference to its source

Environment

No exposure assessment presented for the environment.

ISOPROPANOL 70-100%

Workers

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

For further information on the assessment method, see: <http://www.ecetoc.org/tra>

Only properly trained persons shall make use of scaling methods while checking whether the OC and RMM are within the boundaries set by the ES

Additional good practice advice beyond the REACH Chemical Safety Assessment

Assumes a good basic standard of occupational hygiene is implemented.