

## High Temperature Paper Tape

### DATA SHEET

**Type: M68**

<b>Base film:</b>	High temperature resistant paper
<b>Color:</b>	Yellow
<b>Adhesive:</b>	Rubber
<b>Total thickness:</b>	180+/-5 micron
<b>Peel strength:</b>	>0.28KN/M
<b>Initial tack:</b>	>10# (ball test)
<b>Holding power:</b>	> 15h
<b>Temperature:</b>	160 degree C x 30min
<b>Package</b>	
<b>Core:</b>	Plain paper core / 3"
<b>Length:</b>	50m

**APPLICATION:**

Surfaces to be bonded must be clean, dry and free from dust. Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the company are made in good faith but cannot over-ride the basic obligation of the user to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.

Physical properties listed above are average values and are not to be construed as specifications. Suggestions and recommendations for use are based on tests we believe to be reliable. Purchasers, however, must determine the suitability of the products for their intended use.

Grove Sales Limited assumes no liability for claims beyond the replacement value of our product proven to be defective