



Supplied by

Grove Sales

Quality Products- Reliable Service -Est 1990

Weller®



Fume extraction Zero Smog 4V with Kit 1 Funnel

Item No: T0053662699N

Fume extraction Zero Smog 4V with Kit 1 Funnel

Breathe clean air without dangerous fumes and particles. Weller filtration systems are specially designed for continuous use in industrial work environments. The high quality HEPA H13 filters clean the air from hazardous vapors, particles and viruses. Therefore, recirculating the clean air back into the workplace ensuring a safe work environment. The small footprint design fits under the bench to free up the operator workspace. At only 53db or below, Weller Zero Smog filtration units keep the workplace quiet.



KEY FEATURES

- + Energy-efficient fume extraction system purifies air at up to 4 workplaces, included funnel nozzle for applications where a larger area needs to be covered and the funnel nozzle can be placed directly on the work bench
- + Equipped with HEPA H13 particle filter and fine dust pre-filter F7
- + Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- + Electronic filter control with optical and acoustical filter alarm
- + Low noise emission levels for quiet workspace
- + RS232 port, can be remotely controlled via remote control (optional accessory) or by a PC with RS232 connection
- + Efficiency test via USB port
- + 4 casters to allow easy movement of the unit
- + For connection to a WX / WT station a T0058768767 WT Hub is needed

TECHNICAL DATA

Width	325.0 mm
Height	505.0 mm
Length	345.0 mm
Dimensions L x W x H	345.0 x 325.0 x 505.0mm
Compact Filter	Particle filter H13, broadband gas filter (50% activated carbon + 50% Chemisorb)
Compatible Nozzle	WX WT
ESD Safe	Yes
Maximum Blower Vacuum (Pa)	3,800 Pa
Maximum Capacity	1-4 Workstations
Power	275 VA
UPC	037103273420
USB	The USB port can be used to load firmware updates, run efficiency tests and log data. Do not leave the USB medium inserted for longer than 2 minutes. After this time expires, the USB module will switch off automatically.